



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			
Built date	1966	Length (strikers)	77'-4"	Truck type	ASF, Ride control A3	Draft Gear	NA
Car builder	Thrall	Coupled length	79'-10"	Bols. Patt. / AAR Code	ASF, 72245-K	Cushioning	Freight Master
AFE number	66-103	Truck ctrs.	61'-4"	Side Frame/AAR Code	ASF, 72415-F	Brake system	Body mounted
AAR Mech. Des.	NA	Length between bulkheads	70'-0"	Truck spring group	ASF, 7(O) 5(I)	Control valve	Wabco, ABD
AAR Car Code	NA	Width bulkhead	8'-10 3/4"	Snubbing type	NA	Brake cylinder	Westinghouse, B-3-8 1/2"
GST Code	NA	Height bulkhead	10'-7 1/2"	Snub. sprng. group	NA	Slack adjuster	NA
Clearance plate	C	Extreme width	9'-8 1/4"	Column wear plate	NA	Brake beam	go Malleable, unit #18,B-493-A
C.G. - Empty	NA	Extreme height	14'-10 5/16"	Pedestal roof liners	NA	Brake beam wear elim.	Unit Truck, UW-133-C
C.G. -loaded	NA	Gross rail load	263,000 lbs.	Wheels	Bethlehem Stil. H-36"	Brake shoes	NA
Min. curve-Coupled	NA	Lightweight	87,200 lbs.	Roller bearing	Tinklen, 6 1/2x12 E-24322-J	Handbrake	Univ., 7420-2-A
Min. curve-Uncoupled	NA	Load limit @ 263K	175,800 lbs.	Adapter	Gen. Std. Co., 6 1/2x12 AM-45125	Floors	2 1/2" fir, treated
Braking ratio - Empty	NA	Floor rating	NA	Truck side bearing	double roller 688-B	Lading anchors	Brandon, C2-1969
Braking ratio - Loaded	NA	Floor Height(light car)	4'-2 13/16"	Horz. center plate liner	NA		
Braking ratio - H.B.	NA			Vertical wear ring	NA		
				Coupler/Knuckle	ASF, Type E		
				Yoke	ASF, Type F		
				Draft sill/Striker assy.	Fabricated		
				Front draft lug	Fabricated		
				Rear draft lug	Fabricated		
				Center plate	Clifford Jacobs, BP-4621 14" dia.		
				Cp. carr. wear plt.	NA		
				Uncoupling rod	Standard RWY. Equip.		
<b>FORMER ROAD NUMBERS</b>							
GN 160535-160539							
<b>NOTES AND EXCEPTIONS:</b>							